

Hazard Register



Type	EXCAVATOR	Location	-
Make	SUMITOMO	Sale Number	5053293
Model	SH210-5	Lot Number	1
Serial Number			

ID	Hazard Type	Hazard Description
138039.1	Emergency Stop	REFER TO THE MANUFACTURERS MANUAL TO ENSURE THE OVER RIDE SAFETY STOPPING DEVICE IS FUNCTIONING CORRECTLY FOR THIS PLANT. EMERGENCY STOP BUTTONS ARE PRESENT ON THIS PLANT. CHECK FOR CORRECT OPERATION OF THE EMERGENCY STOP BUTTON PRIOR TO USE IN THE WORKPLACE.
138039.2	Skills	ENSURE ONLY COMPETENT/SKILLED PERSONNEL HAVE ACCESS TO AND USE OF PLANT. ENSURE RECORDS OF QUALIFICATIONS ARE RETAINED ONSITE.
138039.3	Visibility	ENSURE VISION IS NOT IMPAIRED. REVERSE MIRRORS ARE PRESENT BUT NEED TO BE RE-INSTALLED ON THIS PLANT. WINDSCREENS PRESENT AND GOOD CONDITION ON THIS PLANT.
138039.4	Fire	OPERATOR MUST BE FAMILIAR WITH THE LOCATION AND OPERATION OF THE MAIN ISOLATING SWITCH. ENSURE A FIRE SUPPRESSION SYSTEM IS FITTED TO THIS PLANT (NOT PRESENT ON THIS PLANT). ENSURE PERSONNEL ARE PROVIDED WITH COMPETENCY BASED TRAINING REGARDING USE OF FIRE SUPPRESSION SYSTEM. ENSURE THAT THE FIRE SUPPRESSION SYSTEM IS INSPECTED EVERY 12 MONTHS.
138039.5	Crushing	COMING INTO CONTACT WITH MOVING PARTS OF THE PLANT DURING TESTING, INSPECTION, OPERATION, MAINTENANCE, CLEANING AND REPAIR. ENSURE SIGNAGE IS ATTACHED ADJACENT TO PLANT INSTRUCTING OPERATOR TO "KEEP BODY PARTS (HANDS ECT) CLEAR DURING PLANT OPERATION.
138039.6	Plant Operation	COLLISION. ENSURE THAT THERE IS ONE AUDIBLE AND ONE VISUAL WARNING DEVICE ON THE PLANT. THE ROTATING WARNING LIGHT AND THE MOTION WARNING DEVICE ARE BOTH WORKING ON THIS PLANT.
138039.7	Plant Operation	INJURY TO OPERATOR, PLANT DAMAGE OR FAILURE MAY RESULT FROM OPERATING PLANT ABOVE ITS MAXIMUM WORKING GRADE OR ON AN UNSTABLE SURFACE. ENSURE PLANT IS OPERATED WITHIN MANUFACTURERS SPECIFICATIONS / RECOMMENDATIONS. THERE IS NO MANUFACTURERS MANUAL IN THE CAB OF THIS PLANT.
138039.8	Operator Error	MAY OCCUR DUE TO OPERATOR OVERLOADING / EXCEEDING TRUCK CARRYING CAPACITY/SAFE LOADING LIMIT. ENSURE SAFE LOAD LIMITS ARE CHECKED AND ADHERED TO BY OPERATOR DURING VEHICLE LOADING. MANUFACTURERS MANUAL PRESENT ON THIS PLANT.
138039.9	Safe Working Load	ENSURE SAFE WORKING LOAD LABELS OR ENGINEER COMPLIANCE PLATE PRESENT. AN EMPLOYER MUST ENSURE THAT THE SAFE WORKING LOAD (SWL), INDICATING THE LIFTING CAPACITY IN METRIC UNITS , IF APPROPRIATE, IS CLEARLY LEGIBLE AND FIXED IN A VISIBLE LOCATION AND THAT ALL LIFTING IS DONE WITHIN THE CAPACITY, AS FAR AS PRACTICABLE.
138039.10	Noise	SOUND PRESSURE LEVELS (SPL) NEEDS TESTING AT OPERATOR STATION. IF SPL GREATER THAN 85 dB(A), CLEAR & VISIBLE WARNINGS MUST BE ATTACHED RE: USE OF HEARING PROTECTION.
138039.11	Signage	OPERATOR INJURY MAY RESULT FROM ILLEGIBLE OR MISSING WARNING LABELS/SIGNAGE (NOISE, PPE, OPERATING INSTRUCTIONS, HOT SURFACES, EXITS, ROTATING FANS, NIP POINTS ETC). REGULAR INSPECTION & REPLACEMENT OF WARNING LABELS (SAFETY DECALS) IS REQUIRED. SIGNAGE IS TO BE COMPLIANT WITH AS 1319 SAFETY SIGNAGE FOR THE OCCUPATIONAL ENVIRONMENT.

Hazard Register



138039.12	Guarding	MOVING PARTS OF PLANT MAY ENTRAP OR CUT BODY PARTS. THE REAR WEIGHT PANELS COVERING THE ENGINE AND HYDRAULIC PUMP ARE NOT ON THE PLANT. ALL FIXED AND OPERABLE GUARDS MUST BE REPLACED AFTER MAINTENANCE/CLEANING ACTIVITIES. GUARDING SHOULD BE IN ACCORDANCE WITH AS4024.1: SAFEGUARDING OF MACHINERY.
138039.13	Falling	FALLS MAY OCCUR WHILE ACCESSING PLANT DUE TO POORLY MAINTAINED OR MISSING HANDRAILS, LADDERS, PLATFORMS OR KICK BOARDS. ENSURE ALL ARE MAINTAINED AND CHECKED DURING DAILY PRE-START CHECK AND ANY DEFECTS DOCUMENTED AND REPORTED BEFORE PLANT USE. NON-SLIP MATERIAL PRESENT ON THE CAB FLOOR.
138039.14	Rollover	ENSURE APPROPRIATE R.O.P.S ROLLOVER PROTECTION IS FITTED TO PLANT IN ACCORDANCE WITH AS:2294 ROLL OVER PROTECTION STANDARD FOR EARTH-MOVING MACHINERY. ROPS AND SEAT BEAT PRESENT ON THIS PLANT.
138039.15	Logbooks	ENSURE THAT A LOGBOOK IS COMPLETED WITH DAILY OPERATIONAL SAFETY CHECKS AND RECORDS OF FAULTS, REPAIRS AND MAINTENANCE. ENSURE LOGBOOK IS RETAINED WITHIN PLANT CABIN.
138039.16	Plant Controls	OPERATOR INJURY MAY RESULT FROM POORLY LABELLED / UNLABELLED OR INCORRECTLY LABELLED CONTROLS. ENSURE ALL OPERATIONAL CONTROLS ARE CLEARLY IDENTIFIED AND LABELED.
138039.17	Flammable substances	EXPLOSION/FIRE FROM ENGINE, SHUT OFF ENGINE AND LEAVE TO COOL BEFORE REFUELING, PROVIDE FIRST AID KIT AND FIRE EXTINGUISHER FOR THE PLANT.
138039.18	Fire	FAILURE OF SERVICE LINES (FUEL, OIL, HYDRAULIC). ALL LINES SHOULD BE REGULARLY INSPECTED FOR ANY VISIBLE SIGNS OF DAMAGE AND REGULARLY SERVICED AND MAINTAINED.
138039.19	HIGH PRESSURE	PLANT FAILURE. ENSURE THAT ALL HYDRAULIC LINES, HOSES AND CONNECTIONS ARE INSPECTED AND REPAIRED IF DAMAGED.
138039.20	overhead obstruction	ELECTROCUTION – ENSURE OPERATORS ARE AWARE OF POTENTIAL HAZARDS (IE) OVERHEAD ELECTRICAL LINES AND ENSURE OVERHEAD ZONING LABEL (DECAL) IS PRESENT IN CABIN.
138039.21	Vibration	OPERATOR MAY BE EXPOSED TO EXCESSIVE OR WHOLE BODY VIBRATIONS DURING PLANT OPERATION. ENSURE OPERATORS SEAT IS MAINTAINED AND IN GOOD CONDITION. REPLACE DAMAGED OR WORN SEAT.
138039.22	Pre-operational check	DEVELOP AND CONDUCT (DAILY) DOCUMENTED PRE-OPERATIONAL CHECKS PRIOR TO EACH USE. ENSURE DEFECTS ARE REPORTED AND DOCUMENTED COPIES ARE RETAINED WITH PLANT.

Health and Safety Plant Safety Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

Likelihood	Consequences
<ul style="list-style-type: none">• Frequency and duration of exposure• Probability of occurrence of hazard or event (including part history of incidents)• Possibility to avoid / minimize or limit the damage, impact or harm• Reliability and effectiveness of existing / established systems of control	<ul style="list-style-type: none">• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support• Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured• Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point• Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area• Are temperatures of plant, or chemicals, likely to further injure entrapped person

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.

Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.

High risk – considered to be unacceptable and requiring action within the short to medium term.

Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.