

# Hazard Register



Type	ROAD SWEEPER TRUCK	Location	
Make	SCHMIDT	Sale Number	7047915
Model	250	Lot Number	0002
Serial Number		Vendor	127449-2

ID	Hazard Type	Hazard Description
140827.1	Skills	Ensure only competent / skilled personnel have access to and use of plant.
140827.2	Plant Operation	Ensure operator is provided with Standard Operating instructions - attach instruction in a clear and prominent position at operator's station.
140827.3	Emergency Stop	Ensure all emergency stop switches are regularly tested in accordance with the original manufacturer specifications.
140827.4	Noise	Test and ensure sound pressure levels (SPL) are below 85 dB(A) at operator station, if required attach warning labels and ensure PPE is used by operators.
140827.5	Manual Handling	Operator strains and/or sprains from handling work pieces, product on and off the plant or as a result of repetitive body movements - handling of rear mounted suction hose
140827.6	Plant Malfunction	Ensure all malfunction alarms , warning and monitoring devices are functioning.
140827.7	Guarding	All plant interlocks should be routinely tested and inspected (cleaned to be free of dust and extraneous matter)
140827.8	Crushing	Ensure all operators are trained and made aware of crush/pinch hazards. Ensure crush/ pinch warning labels are attached.
140827.9	High Pressure Fluid	Person may come into contact with fluids under high pressure, due to plant failure or misuse of the plant.
140827.10	Guarding	Moving parts may entrap or cut body parts. All fixed and operable guards must be replaced after maintenance / cleaning activities. Guarding should be in accordance with standard
140827.11	Signage	Operator injury may result from illegible or missing warning labels/signage (noise, PPE, operating instructions, hot surfaces, exits, rotating fans, nip points etc). Regular inspection and replacement of warning labels (SAFETY DECALS) is required.
140827.12	Plant Maintenance	Ensure plant is isolated, de-energised before commencing cleaning and/or maintenance activities.
140827.13	PPE	Operator injury resulting from not wearing provided PPE, wearing poorly maintained PPE, wearing insufficient or inappropriate PPE
140827.14	Plant Controls	Operator injury can result from poorly labelled/ unlabelled or incorrectly labelled controls. Ensure all operational controls are clearly identified and labelled.

## Health and Safety Plant Safety Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

Likelihood	Consequences
<ul style="list-style-type: none"><li>• Frequency and duration of exposure</li><li>• Probability of occurrence of hazard or event (including part history of incidents)</li><li>• Possibility to avoid / minimize or limit the damage, impact or harm</li><li>• Reliability and effectiveness of existing / established systems of control</li></ul>	<ul style="list-style-type: none"><li>• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support</li><li>• Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured</li><li>• Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point</li><li>• Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area</li><li>• Are temperatures of plant, or chemicals, likely to further injure entrapped person</li></ul>

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.

Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.

High risk – considered to be unacceptable and requiring action within the short to medium term.

Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.