

Hazard Register



| | | | |
|---------------|-----------|-------------|------|
| Type | FUEL TANK | Location | |
| Make | - | Sale Number | 1967 |
| Model | - | Lot Number | |
| Serial Number | | | |

| ID | Hazard Type | Hazard Description |
|-----------|-----------------|---|
| 142894.1 | Chemicals | ENSURE THAT THE JSA INCLUDES AN ASSESSMENT OF REMOVAL OF RESIDUAL CHEMICALS. REVIEW STORAGE/DISPOSAL, MATERIAL SAFETY DATA SHEETS AND PERSONAL PROTECTIVE EQUIPMENT REQUIREMENTS. |
| 142894.2 | Plant Operation | OPERATOR MUST BE FAMILIAR WITH THE LOCATION AND OPERATION OF THE MAIN ISOLATING SWITCH AND FIRE FIGHTING APPLIANCES/SERVICES. |
| 142894.4 | Plant Operation | NO OPERATING INSTRUCTIONS AVAILABLE FOR THE PLANT. PROVIDE TRAINING AND ATTACH INSTRUCTIONS IN A CLEAR AND VISIBLE POSITION FOR THE OPERATOR. |
| 142894.7 | Mechanical | POWER SUPPLY TO THE PLANT MUST BE ISOLATED, DENERGISED BEFORE COMMENCING ANY CLEANING AND OR MAINTENANCE ACTIVITIES. |
| 142894.8 | Plant Structure | RESTRICT ACCESS TO INSIDE TANKS. ENSURE CONFINED SPACE ENTRY SYSTEM IS FOLLOWED. |
| 142894.9 | Chemicals | ENSURE NO SMOKING AND NO IGNITION SOURCES WITHIN THE VICINITY OF THE PLANT. IN PARTICULAR WHEN FILLING AND OR RE-FUELLING VEHICLES. PROVIDE PPE AS APPLICABLE. THERE IS NO DANGEROUS GOODS CLASS SIGN ON THIS PLANT. ENSURE THE RELEVANT CLASS SIGN IS DISPLAYED ON THE TANK. |
| 142894.10 | Fire/Explosion | ENSURE THAT A METHOD OF FIRE SUPPRESSION IS ASSOCIATED WITH THE TANK. ENSURE THAT THE FIRE SUPPRESSION UNITS (OR FIRE EXTINGUISHER) ARE INSPECTED EVERY SIX MONTHS. |
| 142894.13 | Plant Operation | ACCESS TO BE RESTRICTED TO AUTHORISED AND TRAINED PERSONNEL ONLY. FIT HAZARD WARNING SIGNS (AS APPROPRIATE) TO PREVENT ACCESS TO DANGER ZONES. |
| 142894.14 | Plant Operation | NO SERVICE/MAINTENANCE RECORDS AVAILABLE. REQUIRES REGULAR DOCUMENTED CONDITION INSPECTIONS (INCL SAFETY RELATED CONTROLS). |
| 142894.15 | Plant Structure | PREPARE JOB SAFETY ANALYSIS (JSA) TO ASSESS AND CONTROL HAZARDS ASSOCIATED WITH DISMANTLING, TRANSPORT AND STOWING OF PLANT. |

Health and Safety
Plant Safety
Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

| Likelihood | Consequences |
|--|---|
| <ul style="list-style-type: none">• Frequency and duration of exposure• Probability of occurrence of hazard or event (including part history of incidents)• Possibility to avoid / minimize or limit the damage, impact or harm• Reliability and effectiveness of existing / established systems of control | <ul style="list-style-type: none">• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support• Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured• Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point• Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area• Are temperatures of plant, or chemicals, likely to further injure entrapped person |

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

- Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.
Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.
High risk – considered to be unacceptable and requiring action within the short to medium term.
Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.