

Hazard Register



Type	GARBAGE TRUCK	Location	
Make	GENERIC	Sale Number	250506
Model	GENERIC.	Lot Number	1
Serial Number			

ID	Hazard Type	Hazard Description
141752.1	Drawing In	Operator, hair, clothing, gloves, jewellery, cleaning brushes, rags or other material being drawn into moving parts of the plant.
141752.2	Signage	Operator injury may result from illegible or missing warning labels/signage (noise, PPE, operating instructions, hot surfaces, exits etc). Regular inspection and replacement of warning labels is required - Signage is to be compliant with AS 1319 Safety Signs for the Occupational Environment
141752.3	Manual Handling	Operator strains and/or sprains from handling work pieces, product on and off the plant or as a result of repetitive body movements - handling of 240ltr wheelie bins/completed bales.
141752.4	Emergency Stop	Identification of emergency stop switches (emergency stop switches should be red mushroom types contrasted by a yellow background)
141752.5	Emergency Stop	Failure of emergency stop switches (all emergency stop switches should be regularly tested in accordance with the original manufactures specifications)
141752.6	Plant Operation	Plant operated by employees without suitable instruction and training. Ensure operators are trained and operating instructions are posted in view of operators.
141752.7	Crushing	Coming in contact with moving parts of the plant during testing, inspection, operation, maintenance, cleaning or repair. Ensure signage has been erected adjacent to plant instructing operator to keep body parts (i.e hands ect) clear during plant operation.
141752.8	Plant Maintenance	Ensure isolating, De-energising of plant is carried out before commencing any cleaning and/or maintenance activities.
141752.9	High Pressure Fluid	Person may come into contact with fluids under high pressure, due to plant failure or misuse of the plant
141752.10	Skills	Ensure only competent / skilled personnel have access to and use of plant.
141752.11	Plant Controls	Unintentional or incorrect operation of plant as a result of poorly labelled/unlabelled or incorrectly labelled controls
141752.12	Guarding	All plant interlocks should be routinely tested and inspected (cleaned to be free of dust and extraneous matter)
141752.13	Noise	Sound pressure levels (SPL) requires testing at operators station. If greater than 85 db (a) clear & visible warnings must be attached re: use of hearing protection.
141752.14	Plant Maintenance	Operation of plant that is in an unsuitable condition (no maintenance schedule, inspection or records)
141752.15	Plant Operation	Operator is not provided with Standard Operating instructions - attach instruction in a clear and prominent position
141752.16	PPE	Operator injury resulting from not wearing provided PPE, wearing poorly maintained PPE, wearing insufficient or inappropriate PPE
141752.17	Guarding	Moving parts may entrap or cut body parts. All fixed and operable guards must be replaced after maintenance / cleaning activities. Guarding should be in accordance with AS 4024 safe guarding of machinery.

Health and Safety
Plant Safety
Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

Likelihood	Consequences
<ul style="list-style-type: none">• Frequency and duration of exposure• Probability of occurrence of hazard or event (including part history of incidents)• Possibility to avoid / minimize or limit the damage, impact or harm• Reliability and effectiveness of existing / established systems of control	<ul style="list-style-type: none">• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support• Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured• Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point• Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area• Are temperatures of plant, or chemicals, likely to further injure entrapped person

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

- Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.
Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.
High risk – considered to be unacceptable and requiring action within the short to medium term.
Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.