

Hazard Register



Type	JIB CRANE	Location	
Make	-	Sale Number	1967
Model	-	Lot Number	
Serial Number			

ID	Hazard Type	Hazard Description
143065.1	Electrical	PLANT TO BE USED IN CONJUNCTION WITH EARTH LEAKAGE CIRCUIT BREAKER (SAFETY SWITCH) AND OVERLOAD PROTECTION.
143065.2	Plant Structure	ENSURE PLANT IS OPERATED AND MAINTAINED AS PER MANUFACTURER'S INSTRUCTION E.G. VERIFY/CONFIRM MODIFICATIONS TO THE PLANT PRIOR TO USE
143065.3	Plant Operation	ENSURE MAINTENANCE OR SERVICE RECORDS ARE MADE AVAILABLE, DOCUMENT REGULAR INSPECTION/MAINTENANCE FOR THE PLANT
143065.4	Labelling	ATTACH CLEAR & VISIBLE LABELS IDENTIFYING ALL OPERATING CONTROLS.
143065.5	Falling Objects	ENSURE OBJECTS LIFTED BY CRANE ARE SECURED APPROPRIATELY TO PREVENT THE POTENTIAL FOR FALLING OBJECTS
143065.6	Skills	PLANT SHOULD BE USED AND ACCESSED BY COMPETENT/SKILLED (OPERATOR) PERSONNEL ONLY.
143065.7	Plant Operation	PLANT TO BE OPERATED IN DESIGNATED AREAS ONLY (I.E. FIRM/STABLE/LEVEL GROUND).
143065.8	Guarding	ENSURE GUARDING OF PLANT IS IN ACCORDANCE WITH AS 4024 SAFETY OF MACHINERY.
143065.9	Manual Handling	DOCUMENT MANUAL HANDLING RISK ASSESSMENT OF ALL MANUAL HANDLING TASKS ASSOCIATED WITH THE PLANT
143065.10	Plant Operation	ATTACH OPERATING INSTRUCTIONS IN A CLEAR AND VISIBLE POSITION TO OPERATOR
143065.11	Signage	SAFE WORKING LOAD LABEL SHOULD ALWAYS BE ATTACHED TO THE PLANT.
143065.12	Electrical	PLANT NEEDS TO BE REGULARLY INSPECTED AND MAINTAINED AS PER AS/NZS3760: IN-SERVICE SAFETY INSPECTION AND TESTING OF ELECTRICAL EQUIPMENT AND AS/NZS3000: WIRING RULES AND/OR AS1543: ELECTRICAL EQUIPMENT OF INDUSTRIAL MACHINES.

Health and Safety Plant Safety Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

Likelihood	Consequences
<ul style="list-style-type: none">• Frequency and duration of exposure• Probability of occurrence of hazard or event (including part history of incidents)• Possibility to avoid / minimize or limit the damage, impact or harm• Reliability and effectiveness of existing / established systems of control	<ul style="list-style-type: none">• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support• Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured• Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point• Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area• Are temperatures of plant, or chemicals, likely to further injure entrapped person

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.

Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.

High risk – considered to be unacceptable and requiring action within the short to medium term.

Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.