



KENWORTH TRUCKS

A DIVISION OF **PACCAR** AUSTRALIA PTY. LTD.

A.B.N. 43 004 669 667

64 Canterbury Road, Bayswater
P.O. Box 60, Bayswater, Victoria 3153, Australia
Telephone: (03) 9721 1500
Fax: (03) 9720 4144



30 January 2024

TO WHOM IT MAY CONCERN

Reference: Kenworth VIN 6F5000000BA445088

The current applicable ratings for this vehicle as manufactured by Kenworth Trucks for general on-highway operations are:

Gross Train Combination Mass up to and including 70.0 tonnes and/or
Gross Vehicle Mass up to and including 24.70 tonnes
(Lesser of Component Gross Vehicle Mass up to 24.70 tonnes, or,
ADR braking certification Gross Vehicle Mass of 26.5 tonnes)

The vehicle specifications as manufactured by Kenworth Trucks were as follows, shown with current applicable component ratings:

Model	: T403	Date of Manufacture:	August 2011
Engine	: Cummins ISX EGR ADR80/03-450	Governed rpm:	2000
S/N	: 79467007		
Max Power	: 347 kW @ 1600 rpm		
Max Torque	: 2237 Nm @ 1150 rpm		
Transmission	: Fuller RTLO18918B		
Ratios	: 14.40 12.29 8.51 7.26 6.05 5.16 4.38 3.74 3.20 2.73 2.28 1.94 1.62 1.38 1.17 1.00 0.86 0.73		
Tailshaft	: Meritor RPL25		
Steer Axle	: Meritor FG941LA	Rating:	6600 kilograms
Front Suspension	: Kenworth Leaf Spring 7.2t	Rating:	7200 kilograms
Steer Tyres	: 295/80R22.5	Rating:	6900 kilograms
Steer Wheels/Rims	: 8.25 x 22.5 285PCD Alloy Wheels	Rating:	6600 kilograms
	Front Axle Assembly Rated Capacity:		6600 kilograms
Drive Axles	: Meritor RT46-160GP	Rating:	20900 kilograms
Drive Axle Ratio	: 4.30		
Rear Suspension	: Kenworth Airglide 400 Tandem, Alloy	Rating:	18100 kilograms
This airbag suspension system has been certified as Road-Friendly by the Federal Office of Road Safety (FORS). Certificate No. RF2023			
Drive Tyres	: 11R22.5	Rating:	21800 kilograms
Drive Wheels/Rims	: 8.25 x 22.5 285PCD Alloy Wheels	Rating:	26400 kilograms
	Rear Axle Assembly Rated Capacity:		18100 kilograms
Wheelbase	: 4650 mm	Chassis Section:	270 x 89 x 8mm High Tensile Steel (with rear suspension insert only)
Rear Overhang	: 1370 mm		

The maximum recommended operating speed is 100 km/h, for which suitable tyres must be fitted. The maximum geared road speed of this vehicle was 123 km/h, Road Speed Limited to 100 km/h.

HOLLAND FW351 X2 fifth wheel (D-Rating 165 kN) and fifth wheel mounting angles were fitted by Kenworth Trucks as original equipment, attached in accordance with Kenworth Engineering Specifications.



Please note that the above statements :

- do not affect the terms of any existing warranty in respect of this Kenworth truck
- are not a separate warranty by Kenworth Trucks
- are not separate application approval for any specific use of this Kenworth truck.

This vehicle was fitted with an Approved ADR Compliance Plate, in accordance with ADR61.

Compliance of the identified Category NC vehicle is confirmed by the Approval Number stamped in the upper left corner of the plate.

Individual ADR numbers are no longer required to be identified where an Approval Number is provided, excepting ADR64 (Roadtrains and B-Doubles). This compliance, if applicable, is shown on the Vehicle Identification Plate.

This vehicle is certified to ADR64 for Road Train and/or B-Double prime mover use (State permit requirements may be greater than ADR64 standards).

No authorisation exists for other Engineering Signatories to rate or approve this original specification Kenworth truck above the ratings stated in this letter (Vehicle Standards Bulletin No.6, Section S).

Any modification to certified components made after manufacture must be approved by an authorised Engineering Signatory and may vary the above ratings.

VSB6 (Part A, Section A, 4.4) stipulates that "requirements of the ADR's and original manufacturer's modification guidelines shall take precedence". As Kenworth Trucks offers a wide range of alternative manufacturer's original specifications, Kenworth Trucks can provide manufacturers ratings for most modifications (VSB6, Section S, Code S1).

Yours faithfully,
KENWORTH TRUCKS

A handwritten signature in blue ink, appearing to read 'Chevinda', is written over a light blue rectangular background.

Chevinda Chevy Karunanayake
Applications Engineer

Reference: Kenworth VIN 6F5000000BA445088