

SMLRO E- bike : C6 – Mountain E-Bike 21 Speed , 26”

Category: Electric mountain bike

Model: C6 - E- BIKE conditions as per cartons received, Specification for reference only

Colors/Quantity (10 Units) : Black/blue(3), black/red(2), black/green(1), white/blue(2), white/red(2)

Frame: 6061 aluminum alloy

Front fork: SMLRO aluminum alloy shoulders suspension fork

Driving modes: Pure electric(5 shifts), Electric assist(5 shifts), Pure human riding

Battery: Removable lithium-ion battery(CE, ROHS, UL)

Capacity: 48V 13Ah

Range in pure electric mode: 60 km Range in electric assist mode: 90 km

Charging methods: Charge directly or take the battery out for charging

Charger: Local standard input 100~240V AC, output 54.6V 2A, overvoltage, overcurrent, short circuit protection

Charging time: 5-7 hours

Motor: Rear drive 350W/500W/750W/1000W high speed, brushless, toothed, low resistance and low noise motor

Controller: Intelligent sine wave integrated IC control chip

Accelerator: Rotatable throttle grip/Pedal assist

Headlight & Horn: Integrated LED headlight & horn Meter: LCD display control instrument

Display function: MPH, miles, electricity, shift, error code, etc

Cruise control: 4 levels cruise control Protection level: IP54

Max speed: 35 km/h Gears: 21 speed

Shifter levers: Shimano SL-TX30 Front derailleur: Shimano FD-TZ31 Rear derailleur: Shimano RD-TZ500

Cassette: Shimano MF-TZ500, 14-28T Crankset: Prowheel aluminum alloy 24*34*42T

Chain: E-bike optimized, 21 speed

Rims: 26" aluminum alloy double-deck Tires: KENDA 26*1.95" MTB tires Spokes: High rigidity steel

Brake levers: Aluminum alloy, cut off the power to the motor when braking

Brakes: Mechanical disc brakes Handlebar: SMLRO aluminum alloy straight handlebar

Stem : Aluminum alloy Headset: Aluminum alloy CNC

Saddle: Body geometry comfortable sponge saddle

Seat post: Aluminum alloy Pedals: Aluminum alloy Accessories: Kickstand, tools

Max load: 150 kg Net weight: 23 kg Gross weight: 29 kg

