

# Hazard Register



|               |         |             |      |
|---------------|---------|-------------|------|
| Type          | SPRAYER | Location    | -    |
| Make          | -       | Sale Number | 1967 |
| Model         | -       | Lot Number  |      |
| Serial Number |         |             |      |

| ID        | Hazard Type        | Hazard Description  |
|-----------|--------------------|---|
| 143137.1  | Plant Operation    | CONDUCT DOCUMENTED PRE-OPERATIONAL CHECKS PRIOR TO EACH USE, REFER TO MANUFACTURER'S OPERATIONAL/MAINTENANCE MANUALS AS APPLICABLE.   |
| 143137.2  | Plant Operation    | TO PREVENT COLLISIONS WITH OTHER FIXED/MOBILE OBJECTS, USE ALL WARNING SYSTEMS FITTED TO THE PLANT, WHEN THE OPERATION MAY CREATE A HAZARD.   |
| 143137.3  | Signage            | ATTACH CLEAR & VISIBLE HAZARD SIGNS RE KEEP CLEAR OF MOVING PLANT. ENSURE INSTRUCTIONAL AND STRUCK BY WARNING SIGNS PRESENT ON PLANT.   |
| 143137.4  | Plant Structure    | SEEK TECHNICAL ADVICE FROM THE MANUFACTURER BEFORE CARRYING ANY MODIFICATIONS TO THE PLANT. (E.G. ADJUSTMENT TO WHEEL/RIDE HEIGHT, ETC).  |
| 143137.5  | Thermal Conditions | EXPOSURE TO OUTDOOR CLIMATE/WEATHER CONDITIONS. ROTATE WORKERS BETWEEN INDOOR/SHADED AND OUTDOOR/EXPOSED LOCATIONS, PROVIDE PERSONAL PROTECTIVE EQUIPMENT FOR WET, UV EXPOSURE, HOT AND OR COLD CONDITIONS.   |
| 143137.6  | Plant Operation    | MACHINERY TO BE OPERATED BY DESIGNED AND COMPETENT OPERATORS ONLY.  |
| 143137.7  | Plant Operation    | OBTAINT, READ, UNDERSTAND AND FOLLOW MANUFACTURER'S INSTRUCTIONS.   |
| 143137.8  | Process Manual     | SUPPLY SERVICE AND MAINTENANCE RECORDS (IF AVAILABLE).  |
| 143137.9  | Chemicals          | CONDUCT DOCUMENTED CHEMICALS RISK ASSESSMENT FOR ALL CHEMICALS USED WITH THE PLANT.   |
| 143137.10 | Plant Operation    | TO PREVENT COLLISION WITH PEDESTRIANS/BY-STANDERS AND WHEN WORKING NEAR PUBLIC ROADS & ACCESS WAYS, POST WARNING SIGNS AND PLACE BARRIERS ETC AROUND WORKING AREA.  |
| 143137.11 | Noise              | SOUND PRESSURE LEVEL NEEDS TESTING AT OPERATOR WORKSTATION. IF GREATER THAN 85dB(A), EXAMINE WAYS TO REDUCE EMISSIONS FROM THE PLANT AND ATTACH CLEAR AND VISIBLE HAZARD WARNING SIGN RE: HEARING PROTECTION. |
| 143137.12 | Mechanical         | DO NOT STEP ON OR OFF MOVING PLANT, ONLY OPERATE SELF-STARTER MACHINERY FROM THE DRIVING POSITION OF THE DRIVING PLANT.   |
| 143137.13 | Air Quality        | CHEMICAL MIST MAY BE HARMFUL. ENSURE CORRECT PPE. OPERATE PLANT IN A WELL VENTILATED AREA.  |
| 143137.14 | Thermal Conditions | EXPLOSION/FIRE FROM ENGINE, SHUT-OFF ENGINE AND LEAVE TO COOL BEFORE REFUELING, PROVIDE FIRST AID KIT AND FIRE EXTINGUISHER FOR THE PLANT.  |
| 143137.15 | Plant Structure    | PLANT TIP-OVER DURING USE, ALWAYS OPERATE/UNLOAD/LOAD THE PLANT ON FIRM/STABLE GROUND.  |
| 143137.16 | Process Manual     | SUPPLY (IF AVAILABLE) MANUFACTURER'S OPERATING INSTRUCTIONS (INCLUDING PRE-OPERATIONAL CHECKS & PERSONAL PROTECTIVE EQUIPMENT REQUIREMENTS) AT OPERATOR WORKSTATION.  |
| 143137.17 | Mechanical         | ENTANGLEMENT/STRIKING BY WORKPIECES EJECTING FROM AND OR WITH MOVING PARTS OF THE PLANT, THE DRIVE  |

# Hazard Register



TO THE PLANT MUST BE STOPPED/DISCONNECTED AND THE MOVING PARTS OF THE PLANT STOPPED BEFORE MAINTENANCE AND OR REMOVING ANY OBSTRUCTIONS NEAR THE PLANT.

143137.18 Work Space

SLIP/TRIP/FALL DUE TO CLIMATE CONDITIONS, WIPE CLEAR (BEFORE USING THE PLANT) IF THERE IS ANY MUD, OIL OR OTHER OBSTRUCTIONS ON THE PLANT.

143137.19 PPE

PROVIDE INFORMATION/INSTRUCTION ON STORAGE, USE, CARE AND MAINTENANCE OF PERSONAL PROTECTIVE EQUIPMENT. RISK ASSESS AND OBTAIN THE CORRECT PERSONAL PROTECTIVE EQUIPMENT FOR THE CHEMICALS USED ON THIS PLANT.

143137.20 Work Space

ATTACH CLEAR AND VISIBLE HAZARD WARNING SIGN RE WORK NEAR ON STABLE GROUNDS.

143137.21 Entanglement

ENSURE THAT ALL ROTATING SHAFTS ARE GUARDED WITH CONE GUARDING AS PER AS4204 SAFETY OF MACHINERY, INCLUDING THE GEARBOX OUTPUT, UNIVERSAL AND DRIVE SHAFTS.

## Health and Safety Plant Safety Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

| Likelihood   | Consequences  |
|--|---|
| <ul style="list-style-type: none"><li>• Frequency and duration of exposure</li><li>• Probability of occurrence of hazard or event (including part history of incidents)</li><li>• Possibility to avoid / minimize or limit the damage, impact or harm</li><li>• Reliability and effectiveness of existing / established systems of control</li></ul> | <ul style="list-style-type: none"><li>• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support</li><li>• Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured</li><li>• Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point</li><li>• Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area</li><li>• Are temperatures of plant, or chemicals, likely to further injure entrapped person</li></ul> |

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.

Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.

High risk – considered to be unacceptable and requiring action within the short to medium term.

Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.